

Bio-Fuel research at Chalmers

Ingemar Denbratt

Background

- There is a need to reduce the dependence of fossil fuels due to:
 - Global warming
 - Finite resources
- The fossil fuels will be gradually replaced
- There will not be just one alternative
- Viable alternatives must be found and evaluated
- Qualification criteria's:
 - Environmental impact
 - Efficiency
 - Production cost

Fuels for CI engines studied at Chalmers:

- FAME fuels (RME, SME and PME)
- DME
- Dual-Fuel (Diesel/Nat. Gas)

Both experiments and simulations have been performed

FAME



(RME, SME and PME)

Monica Johansson, Junfeng Yang, Valeri Golovitchev and Ingemar Denbratt

32nd Task Leaders Meeting, Nara, July 25 – 29, 2010



	Methods	Unit	EN590 (EU diesel)	RME	SME	PME
Density	D-4052	Kg/m3	840,9	883,3	885,6	874,5
Sulfur	D-5453	mg/kg	23			
Aromatics	D-6591	Weight %	24,3	NA	NA	NA
Flash point	D-93	Deg C	73	154	159	172
CFPP	IP 309	Deg C	-29	-16	-3	13
Viscosity @ 40 deg C	D-445	mm2/s	2,713	4,468	4,215	5,136
Cetane nr	D-613		52,8	53,4	50,4	61,1
Heating value (net)			42,8	37,34	37,32	36,96
Carbon	D-5291	Weight %		77,5	77,3	76,8
Hydrogen	D-5291	Weight %		12,2	11,9	12,6
Oxygen	CHNS-O	Weight %		10,0	9,8	7,6
IBP	D-86	Deg C	184,8	317	321	315
FBP	D-86	Deg C	334	346	337	344
Oxidation stability	EN 15751	h		8,7	5,7	6,8

Experiments




Soot & NO_x emissions

1,2 mg/m³ ~ 0,01 g/kWh (Euro VI)







Soot & NO_x emissions, RME blends



Soot max 0,5 mg/m³ ~ 0,005 g/kWh
NO_x 2 g/kWh


A25



Modeling:

Chemical Compositions of Bio-diesels

Esters	Formulas	RME	PME
methyl palmitate	$C_{17}H_{34}O_2$	4.2%	43.4%
methyl stearate	$C_{19}H_{38}O_2$	1.8%	4.3%
methyl oleate	$C_{19}H_{36}O_2$	61.1%	39.9%
methyl linoleate	$C_{19}H_{34}O_2$	20.0%	10.0%
methyl linolenate	$C_{19}H_{32}O_2$	9.4%	0.3%



Physical models


Rapeseed methyl ester (methyl oleate, $C_{19}H_{36}O_2$)
Diesel oil surrogate (conventional diesel oil)

Chemical composition

Methyl butanoate	$C_5H_{10}O_2$
Methyl decanoate	$C_{11}H_{22}O_2$
Methyl propanoate	$C_{11}H_{22}O_2$
n-heptane	n- C_7H_{16}
Allene	C_3H_4
n-heptane	n- C_7H_{16}
Toluene	C_7H_8

Model description for RME50: DOS/RME 50:50%

Dynamic ϕ -T Parametric Maps




Diesel oil combustion

RME combustion


PME combustion

Comparison Experiments-Modeling

Emission Trends, Volvo D12C fueled with DOS/RME blends



modeling results



experimental results


DME

Henrik Salsing, Valeri Golovitchev and Ingemar Denbratt

32nd Task Leaders Meeting, Nara, July 25 – 29, 2010

Why DME as an alternative fuel?

- High life cycle efficiency



Why DME as an alternative fuel?

- Versatile

Feedstock



Production Process



End User








Experiments, engine

- Volvo D12 C single cylinder heavy duty engine
- Bore x stroke 131 x 150 mm
- Displaced volume 2.02 L
- Common rail system
- Rail pressure >300 bar
- Injector high flow design >2-3 times a standard injector




Experiments - Spray Chamber



Results

-Soot, NO_x and CO


B50, AA20, Diesel piston with DME as fuel



- At low NO_x conditions CO is the major emission from a DME fuelled engine



- Not relevant measuring soot with a smoke meter (AVL415 *e.g.*)
- More sophisticated instruments must be used (μ -soot, DMPS *e.g.*)

B50, AA20, Diesel piston with DME as fuel



Results

-Soot and NO_x




Results

-Piston shape



Simulations in combination with design of experiments

-Find parameters of importance

-Model the influence of the parameters




Experimental investigation



Results

- Influence of piston shape, CO – NO_x




- A DME adapted piston result in significantly lower CO at the same NO_x-level

Dual Fuel

Valeri Golovitchev

Modeling of Dual Fuel, D-F, Combustion

Operational principle of D-F Diesel engine



a) Air intake and natural gas injection

b) Compression of air/natural gas mixture

c) Pilot diesel oil injection/ignition

Courtesy of: Yutaka Murata

Modeling of Dual Fuel, D-F, Combustion


Computational models

Turbulence model	RNG k- ϵ model
Atomization model	KH-RT model
Collision model	Droplet trajectories
Diesel combustion	PaSR /DOS+nat gas
Flame propagation	TFC/Premix, Chemkin-2
NO _x formation	Extended Zeldovich
Combustion model	Coupled DOS/nat gas

**Natural gas is considered as a blend of 87.8% CH₄, 5.9% C₂H₆, 4.6% C₃H₈, 1.7% C₄H₁₀
Chemical (coupled) mechanism: 76 species, 378 reactions**

Preliminary results; Full cycle simulation

D-F (natgas/diesel) Combustion CA = -1.599911e+02



Summary FAME fuels:

- FAME fuels reduces soot emissions but increases NO_x
- FAME fuels with a higher amount of saturated hydrocarbons (PME) shows a smaller increase in NO_x
- Low blends of RME in Diesel oil can give slightly lower NO_x emissions (not captured by the simulations)
- A relatively good agreement between simulations and experiments was found

Summary DME:

- DME is an alternative fuel with a large potential
- The first DME adapted combustion system has been developed but it still suffers from too high CO emissions
- Further research and development is needed to improve and optimize the performance of DME combustion systems

Summary D-F modeling:

- A model for dual-fuel combustion (pilot Diesel Oil/Natural Gas) was developed
- D-F combustion for operational conditions similar to a conventional Diesel engine was predicted with a similar efficiency.
- Late cycle premixed combustion is presently too slow

Acknowledgements

The Swedish Energy Agency and the Combustion Engine Research Centre (CERC) at Chalmers for funding the projects

Thank you for your attention